

The latex-lab-testphase-new-or-2 code

Frank Mittelbach, L^AT_EX Project

v0.86c 2025-02-26

Abstract

This code implements changes to the output routine intended to be moved in the L^AT_EX kernel at some point in the future.

1 Introduction

2 The Implementation

1 (*package)

2.1 File declaration

```
2 \ProvidesPackage{latex-lab-testphase-new-or-2}
3     [\lftlabneworIIDate\space v\lftlabneworIIversion\space
4     Changes to the output routine]
```

2.2 \@makecol reimplementation

footnote-floats (*plug*) If \DocumentMetadata is used we use footnote-floats as the default. In 2e compatibility mode this should be changed to footnote-floats-legacy.

```
5 \AssignSocketPlug {build/column/outputbox}{footnote-floats}
```

\@makecol@handlesplitfootnotes This is only an early draft and doesn't do much. Contains incomplete preparation for tagging commented out.

\@makecol@splitfootnotemessagehook

TODO: Interfaces and code will change in the future

```
6 \def\@makecol@handlesplitfootnotes {%
7 % \ifx\splitfootnote@continuation\@empty \else
8 % \setbox\footins\ vbox{\splitfootnote@continuation\unvbox\footins}%
9 % \global\let\splitfootnote@continuation\@empty
10 % \fi
11 \ifnum\insertpenalties>\z@
12 \@makecol@splitfootnotemessagehook
13 % \setbox\footins\ vbox{\unvbox\footins --- END at split}%
14 % \gdef\splitfootnote@continuation {--- START after split}%
15 \fi
16 }
17 %\def\splitfootnote@continuation{}
```

This could issue warning if split footnotes are encountered.

```
18 \let \@makecol@splitfootnotemessagehook \@empty
```

(End of definition for \@makecol@handlesplitfootnotes and \@makecol@splitfootnotemessagehook. These functions are documented on page ??.)

2.3 \@outputpage reimplementaion

We still have to deal with various plug setting for tagging: This needs documentation and moving.

default (*plug*)

```
19 \ExplSyntaxOn
    TODO: where should these plug declarations go? tagpdf?
20 \NewTaggingSocketPlug{build/page/header}{default}
21 {
22   \__tag_hook_kernel_before_head:
23   #2
24   \__tag_hook_kernel_after_head:
25 }
26 \AssignTaggingSocketPlug{build/page/header}{default}
```

default (*plug*)

```
27 \NewTaggingSocketPlug{build/page/footer}{default}
28 {
29   \__tag_hook_kernel_before_foot:
30   #2
31   \__tag_hook_kernel_after_foot:
32 }
33 \AssignTaggingSocketPlug{build/page/footer}{default}
```

default (*plug*)

```
34 \NewTaggingSocketPlug{build/column/outputbox}{default}
35 {
36   \__tag_check_typeout_v:n { ==>>-In~\token_to_str:N \@makecol
37                               \c_space_tl\the\c@page }
38   \tag_mc_add_missing_to_stream:Nn \@outputbox {main}
39 }
```

default (*plug*)

```
40 \NewTaggingSocketPlug{build/column/footins}{default}
41 { \tag_mc_add_missing_to_stream:Nn \footins {footnote} }
The two sockets do nothing (default noop) if we are in lua mode. If not they get the
default assigned
42 \sys_if_engine luatex:F
43 {
44   \AssignTaggingSocketPlug{build/column/outputbox}{default}
45   \AssignTaggingSocketPlug{build/column/footins}{default}
46 }
47 \ExplSyntaxOff
48
```

3 Replacement for the footmisc package

The replacement for footmisc. If the new code is used, we must replace the package if it is loaded by the user:

```
49 \declare@file@substitution{footmisc.sty}{latex-lab-footmisc.ltx}
```

This can be removed the moment the remaining hooks and sockets have been integrated into footmisc, which will probably not happen before the 2025/11 release.

4 Temp stuff that is related but should go to the kernel

This is the code from latex-lab-footnotes.dtx.

```
50 \input{latex-lab-footnotes.ltx}
51 </package>
```

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

A		<code>\insertpenalties</code> 11
<code>\AssignSocketPlug</code>	5	
<code>\AssignTaggingSocketPlug</code>	26, 33, 44, 45	
D		L
<code>\def</code>	6, 17	<code>\let</code> 9, 18
default (plug)	2, 19, 27, 34, 40	<code>\tlabneworIIdate</code> 3
<code>\DocumentMetadata</code>	1	<code>\tlabneworIIversion</code> 3
E		N
<code>\else</code>	7	<code>\NewTaggingSocketPlug</code> 20, 27, 34, 40
<code>\ExplSyntaxOff</code>	47	noop (plug) 2
<code>\ExplSyntaxOn</code>	19	
F		P
<code>\fi</code>	10, 15	Plugs:
<code>\footins</code>	8, 13, 41	default 2, 19, 27, 34, 40
footnote-floats (plug)	<u>5</u>	footnote-floats <u>5</u>
footnotes-floats (plug)	1	footnotes-floats 1
footnotes-floats-legacy (plug)	1	footnotes-floats-legacy 1
		noop 2
		<code>\ProvidesPackage</code> 2
G		S
<code>\gdef</code>	14	<code>\setbox</code> 8, 13
<code>\global</code>	9	<code>\space</code> 3
		sys commands:
		<code>\sys_if_engine_luatex:TF</code> 42
I		T
<code>\ifnum</code>	11	tag commands:
<code>\ifx</code>	7	<code>\tag_mc_add_missing_to_stream:Nn</code>
<code>\input</code>	50 38, 41

