

Attributes

Connectors attributes

Attribute Id	protocol	driver	Attribute label	default value	type	required
FIELD_SEP	all	CSV	Field separator	;	string	
RECORD_SEP	all	CSV	Record separator	\n	string	
ESCAPE_CHAR	all	CSV	Escape character	\\	string	
QUOTE_CHAR	all	CSV	Field delimiter	"	string	
COLUMN_NAMES	all	CSV	Column names in first row	no;yes;no	list	
HPRIM_MAINSEP	all	HPRIM	Hprim main separator		atome	no
HPRIM_SUBSUBFIELDSEP	all	HPRIM	Hprim separator for sub sub fields	&	atome	no
HPRIM_SUBFIELDSEP	all	HPRIM	Hprim separator for sub fields	~	atome	no
HPRIM_REPEATER	all	HPRIM	Hprim separator for repeated fields	^	atome	no
HPRIM_ESCAPECHAR	all	HPRIM	Hprim escape char	\	atome	no
FILENAME	all	XCEL	File Name		atome	no
AutoCommit	DBI	all	Autocommit	0	number	no
RaiseError	DBI	all	RaiseError	1	number	no
PrintError	DBI	all	PrintError	0	number	no
ORACLE_HOME	DBI	Oracle	Oracle Home	--nodefault--	string	
DIRECTORY	FTP	all	Directory		string	
LDAP_ROOTDN	LDAP	LDAP	Ldap root dn		atome	no
AutoCommit	LDAP	LDAP	Autocommit	1	number	no
LDAP_LOGINRULE	LDAP	LDAP	Ldap loginrule (eg cn=*,<ROOT>)	cn=*,<ROOT>	atome	no
DIRECTORY	LFS	all	Directory		string	

Containers Attributs

Attribute Id	protocol	driver	Attribute label	default value	type	M*
SHEETNAME	all	XCEL	Sheet Name		atome	no
STARTCOL	all	XCEL	First Column		atome	no
COLCOUNT	all	XCEL	Columns Count		atome	no
STARTROW	all	XCEL	First Row		atome	no
ROWSCOUNT	all	XCEL	Rows Count		atome	no
TITLESROW	all	XCEL	Titles Row		atome	no
RECORD_TAG	all	XML	Recod tag		string	
LDAP_BASEDN	LDAP	LDAP	Base dn for the container		atome	no
LDAP_BASEFILTER	LDAP	LDAP	Base filter for the container	(objectclass=*)	atome	no
LDAP_DNATTRS	LDAP	LDAP	Default attributes to create DN's for new entries	--nodedefault--	atome	no
LDAP_INSERTATTRS	LDAP	LDAP	Default attributes values for new entries	--nodedefault--	atome	no
LDAP_SIZELIMIT	LDAP	LDAP	Number of entries fetched by a query	0	atome	no
LDAP_TIMELIMIT	LDAP	LDAP	Max duration of a query	0	atome	no
LDAP_INSEPARATOR	LDAP	LDAP	Sep for multiples values when inserting		atome	no
LDAP_OUTSEPARATOR	LDAP	LDAP	Sep for multiples values when fetching		atome	no
LDAP_FIRSTONLY	LDAP	LDAP	For multiples retrieve first one only		atome	no
LDAP_SCOPE	LDAP	LDAP	Scope of the search	sub;sub;base;one	list	no

Webservices Attributes

Attribute Id	Prot*	drv*	Attribute label	default value	type	M*
WS_PORT	all	all	Webservice Port	--nodefault--	number	no
WS_TYPE	all	all	Webservice Type	WS_SOAP;WS_SOAP;WS_XMLRPC	list	no
WS_COMPRESSION	all	all	Webservice Compression threshold	--nodefault--	number	no
WS_HTTPS_CERT_FILE	all	all	Webservice SSL certificat file	--nodefault--	string	no
WS_HTTPS_KEY_FILE	all	all	Webservice SSL key file	--nodefault--	string	no
WS_AUTHTYPE	all	all	Webservice Authentification methode	WS_AUTH_NONE;WS_AUTH_NONE; WS_AUTH_TICKET	list	no
WS_AUTH_TTL	all	all	Webservice Auth. Time To Live in seconds	60	number	no
WS_PROTOCOL	all	all	Webservice Protocol	WS_PROTO_HTTP;WS_PROTO_HTTP; WS_PROTO_TCP;WS_PROTO_POP3	list	no
WS_REUSEPORT	all	all	Webservice Reuse Port	0	list	no

XmlSockets Attributs

Attribute Id	protocol	driver	Attribute label	default value	Data type	required
XS_CHILDCOUNT	all	all	Max number of childs	--nodefault--	list	no
XS_CHILDPORT	all	all	Child port number	--nodefault--	list	no
XS_CLIENTPORT	all	all	Client port number	--nodefault--	list	no
XS_HOSTALLOW	all	all	Hosts allowed to connect	--nodefault--	list	no
XS_HOSTDENY	all	all	Hosts not allowd to connect	--nodefault--	list	no
XS_MAXCHILDMSGSIZE	all	all	Max size of messages from child	--nodefault--	list	no
XS_MAXCLIENTMSGSIZE	all	all	Max size of messages from client	--nodefault--	list	no
XS_MAXMSGSIZE	all	all	Max message size	--nodefault--	list	no
XS_RECSEP	all	all	Record separator (see xmlsocket doc)	--nodefault--	list	no
XS_REUSE	all	all	Reuse port	--nodefault--	list	no
XS_SCRIPTTO	all	all	Script timeout	--nodefault--	list	no