PNG-GROUP-DRAFT
PNF
Expires: 16 Feb 1997

PNG Development Group
mpng-list@dworkin.wustl.edu
16 Aug 1996

Portable Network Graphics Frames Format Proposal Version 0.960816

File

draft-pnf-960816.txt

Status of this Memo

This document is an informal draft of the PNG development group.

It is a **proposal**, and the format is subject to change.

Comments on this document can be sent to the PNG specification maintainers at

`png-info@uunet.uu.net` or at `png-list@dworkin.wustl.edu`.

Distribution of this memo is unlimited.

At present, the latest version of this document is available on the World Wide Web from

`ftp://swrinde.nde.swri.edu/pub/pnf/documents/`.

Changes from tenth draft (draft-pnf-960813)

- Added image_type field to DHDR.
- Added delta_type 2, which means the IDAT should be read as if it were grayscale but use it as deltas on the alpha channel.
- Removed the "default values" from the FHDR chunk specification.
- Removed PND "Other PND chunks" section.
- Specified the conditions under which IHDR and IEND can be omitted from a PND stream.
- Updated the URL for the latest version of this document, above.
- Added PROM chunk.
- Added a remark in the abstract about storing tomographic "voxel" data, and provided an example.

Abstract

This document presents the *[proposed]* the format of a PNF (Portable Network graphics Frames) stream. PNF is a multiple-image format that can contain simple animations (slide shows) comprised of PNG single-image streams. It can also incorporate PND (Portable Network Delta) and composite frames, which are defined herein, and PNP (Portable Network Photo) images, once a definition for PNP is developed.

A PND stream defines an image in terms of a basis PNG, PNP, or PND image and the differences from that image. This can provide a much more compact way of representing subsequent images than using a complete PNG or PNP stream for each.

A composite frame stream defines a single image whose subimages can be PNG, PND, or PNP single-image streams. A composite frame can be independent, or, if it contains PND streams, it can depend upon the information in the previous composite frame. The composite frame format provides a mechanism for using a subimage as a "sprite" that can be moved from one location to another in subsequent dependent composite frames. A composite frame normally contains a two-dimensional layout of smaller images, but it could also contain three-dimensional "voxel" data arranged as a series of two-dimensional planes (or tomographic slices), each plane being represented by a PNG, PNP, or PND.

The PNF and PND formats use the same chunk structure that is defined in the PNG specification, and share other features of the PNG format.

Contents

1 Introduction 2
2 Top-level PNF chunks 3
2.1 Critical PNF chunks 3
2.1.1 `FHDR` PNF stream header 3
2.1.2 `FEND` End of PNF stream 5
2.1.3 `IHDR`, PNG chunks, `IEND` 5
2.1.4 `DHDR`, PND chunks, `DEND` 5
2.1.5 `PHDR`, PNP chunks, `PEND` 5
2.1.6 `CHDR` composite frame chunks, `CEND` 5
2.1.7 `SEEK` Seek point 6
2.2 Ancillary PNF chunks 6
2.2.1 `dISC` Ok to discard 6
2.2.2 `dURa` Duration 7
2.2.3 `tEXt`, `zTXt` Text chunks 7
3 The PND format 7
3.1 PND critical chunks 8
3.1.1 `DHDR` PND stream header 8
3.1.2 `DEND` End of PND stream 9
3.1.3 `PROM` Promotion of basis image 9
3.1.4 `IHDR`, PNG chunks, `IEND` 9

Image replacement . . . 10
Image pixel deltas . . . 10
Image alpha deltas . . . 11
No change to pixel data . . . 11
3.1.5 PHDR, PNP chunks, PEND . . . 11
3.1.6 COPY Chunks to be copied . . . 11
3.1.7 NOCO Chunks not to be copied . . . 12
3.2 PND ancillary chunks . . . 12
3.2.1 fADE fade in or out . . . 12
3.2.2 tEXt, zTXt Text chunks . . . 13
4 The composite frame . . . 13
4.1 Critical composite frame chunks . . . 14
4.1.1 CHDR Composite frame header . . . 14
4.1.2 CEND End of composite frame . . . 14
4.1.3 LOCA Subimage location . . . 14
4.1.4 IHDR, PNG chunks, IEND . . . 15
4.1.5 DHDR, PND chunks, DEND . . . 15
4.1.6 PHDR, PNP chunks, PEND . . . 15
4.1.7 SODE Subimage source and destination . . . 15
4.2 Ancillary composite frame chunks . . . 16
4.2.1 gPLT Global Palette . . . 16
4.2.2 oFFs Composite frame offset . . . 17
4.2.3 tEXt, zTXt Text chunks . . . 18
5 Retaining image data . . . 18
6 Security Considerations . . . 18
7 Appendix: Examples . . . 19
7.1 Example 1: Simple movie . . . 19
7.2 Example 2: Single composite frame . . . 19
7.3 Example 3: Movie with sprites . . . 20
7.4 Example 4: “Fading in” a transparent image . . . 22
7.5 Example 5: Storing three-dimensional images . . . 22
8 Credits . . . 23

1 Introduction

This *[proposed]* specification defines the format of the PNF (Portable Network graphics Frames) stream. It also defines the format of the PND (Portable Network graphics Delta) stream and the format of a single-image, composite frame stream. PND and the composite image stream can be components of a PNF stream.

Note: This *[proposed]* specification depends on the PNG Portable Network Graphics) and PNP (Portable Network Photograph) specifications. PNP is under discussion by pnp-list@dworkin.wustl.edu. The PNG specification is available at the PNG home page,

```
http://quest.jpl.nasa.gov/PNG/
```

A PNF stream describes a sequence of single images, each of which can be composed of one or more PNG, PNP, PND (PNG-Delta, defined herein), or composite images.

PNF is pronounced “Ping-frames.”

When the PNF stream is a standalone file, the first eight bytes are

```
138 80 78 70 13 10 26 10
```

which is similar to the PNG signature with “\212 P N F” instead of “\211 P N G” in bytes 1-4. Use “.pnf” as the file suffix.

PNF does not accommodate sound or complex sequencing information, nor does it accommodate playing a stream backwards. Those are left to be described in the MPNG specification, which is yet to be defined, and is being discussed in the `mpng-list@dworkin.wustl.edu` mailing list.

Chunk structure (length, name, CRC) and the chunk-naming system are identical to those defined in the PNG specification. As in PNG, all integers that require more than one byte will be in network byte order.

A PNF stream consists of a `FHDR` chunk, followed by one or more image definitions, followed by the `FEND` chunk. The first image can be a PNG stream (`IHDR`, PNG chunks, `IEND`), a PNP stream `PHDR`, PNP chunks, `PEND`), or an “initial” composite frame (`CHDR`, composite frame chunks, `CEND`). Subsequent images can be any of these, or a PND stream (`DHDR`, PND chunks, `DEND`), or a “dependent” composite frame. Each chunk of the PNF stream or of any image definition is an independent entity, i.e., no chunk is enclosed in the data segment of another chunk.

2 Top-level PNF chunks

2.1 Critical PNF chunks

2.1.1 `FHDR` PNF stream header

```
4 bytes: max_frame_width  (unsigned nonzero integer)

4 bytes: max_frame_height (unsigned nonzero integer)

4 bytes: max_number_of_frames (unsigned nonzero integer)
         There are not more than max_number_of_frames
         in this PNF stream.

4 bytes: max_chunk_length (unsigned nonzero integer)
         No chunk in this stream, including in any
         included PNGs or PNPs, has a data field
         exceeding this length.

4 bytes: ticks_per_second  (unsigned nonzero integer)
```

```
4 bytes: frame_duration (unsigned integer) in
         ticks.  The time between the beginning of
         displaying one frame until the beginning of
         displaying the next.

4 bytes: total_duration (unsigned integer) in ticks.
         Maximum total duration of the entire
         stream.  The sum of the individual frame_durations
         must not exceed this value (under actual playback
         conditions the display is likely to take longer).

4 bytes: default_gamma (unsigned integer)
         The value of gamma, times 100000, to be assumed
         for any images or subimages in the stream that do
         not supply their own value of gamma.  This default
         gamma value also applies to the background color
         or application-supplied background image, if the
         gamma value for the background is unknown, and is
         the gamma value to be assumed when using the gPLT
         chunk.  If this field is zero, the default_gamma
         is undefined.

1 byte:  max_bit_depth (unsigned nonzero integer)

1 byte:  background_source (unsigned integer)
         0: use the supplied background color
         1: read the current display contents or application
            specified background if possible, but if not
            possible, then use supplied background color
         2: background is not required.

2 bytes: red_background (unsigned integer)

2 bytes: green_background (unsigned integer)

2 bytes: blue_background (unsigned integer)

1 byte:  ok_to_discard (unsigned integer)
         0: image data of each frame must be retained
            until the subsequent frame is processed.
         1: image data may be discarded after processing
            each frame.  This is a promise that this PNF
            stream contains no PNDs or dependent composite
            frames)
```

Any of the FHDR data fields can be set equal to zero, meaning that the value assumes the default value. Encoders are strongly encouraged not to use zeros, especially for the max_frame_width and max_frame_height fields, though, if the information is available when the encoder is writing the FHDR

chunk.

2.1.2 `FEND` End of PNF stream

The `FEND` chunk's data length is zero. It signifies the end of a PNF stream.

2.1.3 `IHDR`, PNG chunks, `IEND`

A PNG (Portable Network Graphics) stream.

See the PNG specification for the format of the PNG chunks.

Any chunks between `IHDR` and `IEND` are written and decoded according to the PNG specification. The image width and height must not exceed `max_frame_width` and `max_frame_height` from the `FHDR` chunk.

2.1.4 `DHDR`, PND chunks, `DEND`

A PND (PNG-Delta) stream.

See Chapter 3, The PND Format, below, for the format of the PND stream. Any chunks between `DHDR` and `DEND` are written and decoded according to the PND format. The image width and height must not exceed `max_frame_width` and `max_frame_height` from the `FHDR` chunk.

2.1.5 `PHDR`, PNP chunks, `PEND`

A PNP (Portable Network Photo) stream.

See the PNP specification [not yet written] for the format of the `PHDR` and PNP chunks.

[It is assumed that the PNP stream will begin with a PHDR chunk and end with a PEND chunk, and it is assumed that the first two fields of PHDR will be unsigned 4-byte integers giving the image width and height. Nothing in this document should be construed to constrain the development of PNP in any way]

The image width and height must not exceed `max_frame_width` and `max_frame_height` from the `FHDR` chunk.

Any chunks between `PHDR` and `PEND` are written and decoded according to the PNP specification. Until PNP is defined, it is acceptable for viewers to display an empty width by height frame when a PNP stream is encountered. Such viewers should, when encountering a `PHDR` chunk, simply skip chunks until a `PEND` chunk is found.

2.1.6 `CHDR` composite frame chunks, `CEND`

A composite frame stream. See Chapter 4, The composite frame, below, for the format of the composite frame stream.

2.1.7 `SEEK` Seek point

A seek point.

```
n bytes: previous (number of bytes since the
         previous SEEK chunk) If previous == 0,
         then the number of bytes is unspecified.

n bytes: next (number of bytes to the next SEEK
         chunk) If next == 0, then the number of
         bytes is unspecified.

n is the length of the SEEK chunk, divided by two.
         n must be either 4 or 8.
```

The `SEEK` chunk is only allowed at positions in the PNF stream where a restart is possible, and no information appearing prior to the `SEEK` chunk (other than the information in the `FHDR` chunk) is required to display the remainder of the stream properly. In addition to providing a mechanism for skipping frames or backspacing over frames, this provides a means of dealing with a corrupted datastream. The viewer would abandon processing and simply look for the next `SEEK` chunk before resuming. Note that looking for a PNG `IHDR` or PNP `PHDR` would not be sufficient because the PNG or PNP stream might be a subimage a of a composite frame rather than a complete frame description.

When n is eight, 32-bit machines will have to interpret "`previous`" as a set of two integers, the first representing the number of complete 4G blocks and the second (the last four bytes of "`previous`") as the remainder, and will have to treat "`next`" similarly.

"`Previous`" and "`next`" are measured from the first length byte of one `SEEK` chunk to the first length byte of another `SEEK` chunk.

Applications are allowed to forget everything preceding the `SEEK` chunk, except for data appearing in the `FHDR` chunk, so new instances of any needed chunks are required. The first frame following the `SEEK` chunk must not be defined by a PND stream or a "dependent" composite frame.

Multiple instances of the `SEEK` chunk are permitted.

2.2 Ancillary PNF chunks

2.2.1 `dISC` Ok to discard

The `dISC` chunk temporarily set "`ok_to_discard`", from the `FHDR` chunk, when "`ok_to_discard`" to one. The `dISC` chunk's data length is zero. The presence of the chunk signifies that decoders may discard the subsequent PNG, PND, PNP, or composite frames after processing, and can rest assured that no PND or dependent composite frames will follow. The effect of the `dISC` chunk remains until a `SEEK` chunk is encountered. When the `dISC` chunk is not in effect, then decoders must keep the image data for possible use in the subsequent PND or dependent composite frame, if the "`ok_to_discard`" `FHDR` field is zero. It is not possible to override "`ok_to_discard`" when "`ok_to_discard`" is not zero.

Multiple instances of the `dISC` chunk are permitted.

2.2.2 `dURa` Duration

Duration of display.

```
4 bytes: duration (unsigned integer), in ticks, using
         the tick length determined from ticks_per_second
         defined in the FHDR chunk.
```

Overrides the value of duration given in the `FHDR` chunk. The value of "duration" will remain in effect until another "dURa" chunk is encountered or until a "`SEEK`" chunk is encountered, when the duration reverts to the value from `FHDR`. Multiple instances of the `dURa` chunk are permitted, but no more than one `dURa` chunk is permitted between any two critical chunks. The `dURa` chunk takes effect immediately; if a `dURa` is encountered after an image has been displayed, the next image can be started after the specified number of ticks have elapsed since the previous image was started.

2.2.3 `tEXt`, `zTXt` Text chunks

Same as PNG. *[Should we also allow the tIME chunk here?]*

3 The PND format

A PND stream describes a single image, by giving the changes from a previous PNG (Portable Network Graphics), PNP (Portable Network Photo), or another PND image. While it is possible for a PND stream to be stored in a standalone file (where the basis image is available in another standalone file), a PND stream will normally be found as a component of a PNF stream or a MPNG (Multiple Portable Network Graphics, yet to be defined) stream.

If the PND stream is a standalone file (not usually the case), the first eight bytes are

```
140 80 78 68 13 10 26 10
```

which is similar to the PNG signature with "\213 P N D" instead of "\211 P N G" in bytes 1-4. Use ".pnd" as the file suffix.

PND is pronounced "Ping-delta."

The decoder must have available a basis (decoded) image from which the original chunk data is known. How the basis image is made available to the decoder is up to the implementation. It could be in a separate file or it could be provided earlier in a PNF datastream. The basis image can be the result of decoding a PNG, a PNP, or another PND stream. If alpha or transparency is present, then the decoder must also have available the original background against which the basis image was displayed, if transparency or alpha are to be composited against the background.

The new image is always of the same basic type (PNG or PNP) as the basis image.

The decoder must not have modified the pixel data in the basis image by applying output transformations such as gAMA or cHRM, or by compositing the image against a background. Instead, the decoder must make available to the PND decoder the unmodified pixel data along with the values for the gAMA, cHRM, and any other recognized chunks from the basis image datastream.

A PND stream consists of a DHDR and DEND enclosing other optional chunks (if there are no other chunks, the decoder simply copies the basis image).

Chunk structure (length, name, CRC) and the chunk-naming system are identical to those defined in the PNG specification. Definitions of compression_type, filter_type, and interlace_type are also the same as defined in the PNG specification.

3.1 PND critical chunks

3.1.1 DHDR PND stream header

```
1 byte: image_type
  0: Image type is unspecified.  An IHDR or PHDR chunk
     must be present.
  1: Image type is PNG.   IHDR may be omitted if no IHDR
     fields are different from those in the basis image
     and delta_type is 0, 1, or 3, and if IHDR would
     otherwise have appeared immediately after DHDR.
  2: Image type is PNP.   PHDR may be omitted if no PHDR
     fields are different from those in the basis image,
     and if PHDR would otherwise have appeared immediately
     after DHDR.
```

The image type, whether given explicitly as 1 or 2 or implied by the presence of an IHDR or PHDR chunk, must be the same as that of the basis image.

```
1 byte: delta_type
  0: image replacement
  1: pixel subtraction, by bytes, modulo 256.
  2: alpha subtraction, by bytes, modulo 256.  The
     IHDR - IEND data are written as a grayscale
     image (color type 0) but the decoded samples
     are to be used as deltas to the alpha samples in
     the basis image.  The basis image must have
     (or be promoted to via the PROM chunk) color
     type 4 or color type 6.
  3: no change to pixel data
```

[We might want to add other delta_types like an interplane Paeth filter]

```
1 byte: copy-safe
  0: This stream contains no changes that would render
     unknown chunks unsafe-to-copy.  All chunks will be
     copied from the previous image unless they are
     mentioned in a NOCO chunk.
  1: This stream contains changes that would render
     unknown chunks unsafe-to-copy.  Such chunks will not
     be copied from the previous image unless they are
     mentioned in a COPY chunk.
```

3.1.2 `DEND` End of PND stream

End of PND stream. This chunk has a zero data length.

3.1.3 `PROM` Promotion of basis image

1 byte: new color_type 1 byte: new bit_depth

The `PROM` chunk must appear ahead of `IHDR`.

[Should we define this chunk, or add the fields to DHDR?]

3.1.4 `IHDR`, PNG chunks, `IEND`

A partial PNG (Portable Network Graphics) stream. The basis image must be a PNG or PNG-based PND.

See the PNG specification for the format of the PNG chunks. The PNG stream must contain at least `IHDR` and `IEND` but may inherit other chunk data from the basis image. Except for IDAT, any chunks appearing between `IHDR` and `IEND` are always treated as replacements or additions and not as deltas.

A gAMA, cHRM, or similar chunk existing in the basis image would not affect the pixel data inherited by this PND stream because they are not used in decoding the pixel data. Applications are responsible for ensuring that the pixel values that are inherited from the previous image have not been transformed in any way after decompressing and unfiltering them.

When processing the oFFs and pHYS chunks, the viewer is responsible for providing the correct background if alpha or transparency is present; when the image size or location changes, the background will not be the same background against which the basis image was composited.

When processing the tRNS chunk, if color_type is 3 and PLTE is not supplied, then the number of allowable entries is determined from the number of PLTE entries in the basis image.

The IHDR chunk can be omitted if all of the IHDR fields would be identical to those in the basis image and the image_type is 1 and delta_type is 0, 1, or 3 in the DHDR chunk, and if the IHDR chunk would otherwise have appeared immediately after the DHDR chunk with no intevening PND chunks such as COPY. The decoder must treat this stream as though the IHDR were present, immediately after the DHDR chunk, with all IHDR chunk data identical to that of the basis image.

The IEND chunk can be omitted, if it would be the last chunk in the PND stream before the DEND.

Image replacement When the delta_type == 0 in the DHDR chunk, the pixel data in the IDAT chunks or in a PNP steam represent a completely new image. In ths case, none of the IHDR data need match that of the basis image.

Image pixel deltas When the delta_type == 1 in the DHDR chunk, the pixel data in the IDAT chunks represent deltas from the pixel data in a basis image known to the decoder.

The image width and height, color_type, and bit_depth must match those of the basis image, and the basis image must have been derived from a PNG stream or from a sequence of PND streams that depend upon a PNG stream, but not from a PNP stream.

The compression method, filter method, and interlace method need not be the same.

[We might want to add a compression_type that uses deflate with the previous image data as a preset dictionary]

The IDAT chunk data contains a filtered and perhaps interlaced set of delta pixel samples. The delta samples are presented in the order specified by interlace method, filtered according to the filter method and compressed according to the compression method given in the IHDR chunk. The actual pixel values are calculated using the method defined in the delta_type field of the DHDR chunk.

When delta_type == 1, an encoder calculates the bytes in the IDAT chunk by subtracting the new image bytes from the basis image bytes, modulo 256. When decoding the IDAT chunk, the new image bytes are obtained by adding the delta bytes to the basis image bytes, modulo 256. This is similar in operation to the PNG SUB filter.

When color_type is 3, the deltas are differences between index values (by bytes), not between color samples.

Image alpha deltas When the `delta_type == 2` in the `DHDR` chunk, the pixel data in the `IDAT` chunks represent deltas from the alpha data in a basis image known to the decoder. The updated alpha samples are calculated in the same manner as the updated pixels samples are calculated when `delta_type == 1`.

The image width and height and the bit_depth must match those of the basis image, but the color type must be 0 (grayscale). The basis image must have an alpha channel or must have been promoted to a type that has an alpha channel. The compression method, filter method, and interlace method need not be the same.

No change to pixel data When the `delta_type == 3` in the `DHDR` chunk, there is no change to the pixel data. If `IHDR` is present, the color_type in the `IHDR` data need match that of the basis image.

When the `delta_type == 3` in the `DHDR` chunk, It is an error for `IDAT` to appear.

3.1.5 `PHDR`, PNP chunks, `PEND`

A partial PNG (Portable Network Photo) stream *[yet to be defined]*.

3.1.6 `COPY` Chunks to be copied

Chunks to be copied

```
4 bytes: chunkname_1
etc.
4 bytes: chunkname_n
```

`COPY` provides a list of chunknames that are to be copied (values inherited) from the basis image, regardless of the copy-safe rules, and regardless of whether the chunk is recognized or not. The number of names is determined from the chunk length, divided by 4.

There can be multiple instances of the `COPY` chunk. `COPY` chunks must appear before `IHDR` or `PHDR` if either is present.

The `COPY` chunk does not specify the placement of chunks within the resulting PNG stream; it merely marks them for copying. The decoder can place them in any order, relative to their order in the basis image, that obeys the chunk-ordering rules for copy-safe chunks given in the PNG specification.

The `COPY` chunk data itself is inherited (unless "COPY" appears in a `NOCO` chunk), so a `COPY` chunk need only appear in the first of a sequence of PND streams, if there are no changes.

If a chunkname appears in a `COPY` chunk and also appears in a `NOCO` chunk, the last instance takes precedence.

Applications that reconstruct a PNG or PNF stream from a PND stream and a basis PNG, PNF, or PND stream should not write the `COPY` chunk to the resulting PNG or PNF stream, because the `COPY` chunk would not be recognized by a PNG or PNF decoder.

It is not an error for a chunkname to appear in the copy list, when that chunk does not appear in the basis image.

3.1.7 NOCO Chunks not to be copied

Chunks not to be copied

```
4 bytes: chunkname_1
etc.
4 bytes: chunkname_n
```

NOCO provides a list of chunknames that are not to be copied (values not to be inherited) from the basis image, regardless of the copy-safe rules, and regardless of whether the chunk is recognized or not. The number of names is determined from the chunk length, divided by 4.

There can be multiple instances of the NOCO chunk. The NOCO chunks must appear before IHDR or PHDR, if either is present.

If a chunkname appears in a COPY chunk and also appears in a NOCO chunk, the last instance takes precedence.

It is not an error for a chunkname to appear in the NOCO list, when that chunk does not appear in the basis image.

Applications that reconstruct a PNG or PNF stream from a PND stream and a basis PNG, PNF, or PND stream should not write the NOCO chunk to the resulting PNG or PNF stream.

The NOCO chunk data itself is inherited (unless "NOCO" appears in a NOCO chunk), so a NOCO chunk need only appear in the first of a sequence of PND streams, if there are no changes.

3.2 PND ancillary chunks

3.2.1 fADE fade in or out

This chunk can be used to "fade" an image in or out against the background, without having to transmit new alpha values.

```
1 byte: (unsigned integer) fade_type
      0: fade out
      1: fade in
      2: fade in but don't change fully transparent
         pixels
2 bytes: (unsigned integer) alpha_delta
```

When "fade_type" is 0, the value of alpha_delta is subtracted from the alpha sample of every pixel in the basis image, but the result is not allowed to fall below zero.

When "fade_type" is 1, the value of alpha_delta is added to the alpha sample of every pixel in the basis image, but the result is not allowed to exceed the maximum alpha value for the image's bit depth.

When "fade_type" is 2, the value of alpha_delta is added to the alpha sample of any pixel in the basis image that has a non-zero value, and the result is not allowed to exceed the maximum alpha value for the image's bit depth.

If color_type is 3, then the value of alpha_delta is added to or subtracted from the alpha values that were defined by the tRNS chunk data in the basis image, and the resulting values become the tRNS data exported to any subsequent image. The maximum alpha value for this color_type is 255, regardless of the bit depth.

If color_type is 0 or 2, the fADE chunk is ignored.

If IHDR is also present, the fADE chunk must appear before IHDR. The fade operation is performed on the image data after decoding the chunks between IHDR and IEND.

3.2.2 tEXt, zTXt Text chunks

The tEXt and zTXt chunks are the same as those in PNG. *[Should we also allow the tIME chunk here?]*

4 The composite frame

A composite frame is a single image, made up of the background (defined by the FHDR chunk) and zero or more subimages, each defined by a PNG, PNP, or PND stream. The LOCA chunk can be used to specify the placement of each subimage within the composite frame.

A composite frame can be an "initial" frame or a "dependent" frame. If it is "dependent" then it requires information inherited from the previous frame, such as the global palette (gPLT) and any PNG, PNP, or PND subimages that are to be redisplayed or that are to serve as the basis for a PND subimage. PNF viewers that process composite frames must be prepared to "remember" any number of such subimages from the immediately previous composite frame.

PNF viewers are expected to recognize and process the PNG pHYs and oFFs chunks encountered in subimages, even though these are ancillary chunks. When the pHYs chunk appears with unit_specifier=0, then that subimage should be scaled to to obtain the desired aspect ratio by scaling the image height and leaving the image width fixed.

4.1 Critical composite frame chunks

4.1.1 CHDR Composite frame header

Beginning of a composite frame.

```
4 bytes: composite_frame_width  (unsigned integer)
         (must match that of the previous frame if
         frame_type = 1, and must not exceed
         max_frame_width in the FHDR chunk)

4 bytes: composite_frame_height  (unsigned integer)
         (must match that of the previous frame if
         frame_type = 1, and must not exceed
         max_frame_height in the FHDR chunk)

4 bytes: x_dimension (unsigned integer),
         corresponding to composite_frame_width, in
         micrometers.  If non-zero, this value is to be
         used when processing pHYs and oFFs chunks
         found in subimages, even if the actual frame
         dimensions are otherwise available.

4 bytes: y_dimension (unsigned integer),
         corresponding to composite_frame_height.

1 byte:  frame_type
         0: Initial frame
         1: Dependent frame
```

4.1.2 CEND End of composite frame

End of composite frame. This chunk has a zero data length.

4.1.3 LOCA Subimage location

Location for the following subimage.

The LOCA chunk gives the position, measured downward and to the right of the upper left corner of the frame, where the following subimage is to be located.

The chunk's contents are:

```
4 bytes: Image position, X axis (signed integer)
4 bytes: Image position, Y axis (signed integer)
```

Negative values are permitted, and denote displacement in the opposite directions. LOCA can specify an image placement that is partially or wholly outside the frame boundaries. In such cases, the resulting subimage must be clipped to fit within the frame, or not displayed at all if it falls entirely outside the frame.

If the subimage contains an oFFs chunk, the subimage's offset is computed with respect to the position defined by the LOCA chunk (convert the oFFs distances to pixel units, and add them to the image position defined by LOCA).

After processing one subimage, the offset values revert to (0,0) until another LOCA chunk is encountered.

4.1.4 IHDR, PNG chunks, IEND

The image width and height are allowed to exceed those given in the CHDR chunk; if so, the image must be clipped to fit them.

4.1.5 DHDR, PND chunks, DEND

The image width and height are allowed to exceed those given in the CHDR chunk; if so, the image must be clipped to fit them.

4.1.6 PHDR, PNP chunks, PEND

The image width and height are allowed to exceed those given in the CHDR chunk; if so, the image must be clipped to fit them.

4.1.7 SODE Subimage source and destination

```
1 byte: source
        0: none (subimage will be completely defined
           in this frame by a PNG or PNP stream)
        1: subimage defined in previous frame.  It is
           an error to set source=1 when ok_to_discard
           from the FHDR chunk or dISC chunk is not
           zero.
        2: subimage previously defined in this frame

1 byte: destination
        0: discard immediately after displaying subimage
        1: keep (make available for use by next PNF) It
           is an error to set destination=1 when
           ok_to_discard from the FHDR chunk or dISC
           chunk is not zero.
        2: discard after completion of this PNF
```

```
2 bytes: source ID (unsigned integer)
        when source=0: omitted
        when source=1: subimage identified by
           "destination ID" in the previous frame
        when source=2: subimage identified by
           "destination ID" earlier in this frame

2 bytes: destination ID (unsigned integer)
        when destination=0: omitted
        when destination=1: the "source ID" by which
            this subimage can be identified later in
            this frame or in the following frame
        when destination=2: the "source ID" by which
            this subimage can be identified later in
            this frame.
        Can be the same as the destination ID of a
            previous subimage, if the previous subimage
            will no longer be required.
```

If a SODE chunk is not followed by a subimage description (IHDR, DHDR, or PHDR), i.e. a CEND chunk or another SODE chunk is encountered prior to encountering any IHDR, DHDR, or PHDR chunk, then the subimage from the previous frame with the specified source ID is given the specified destination ID and is retained for possible use in the following frame, but is not displayed in the present frame.

If a subimage header chunk (IHDR or PHDR) is not preceded by a SODE chunk (i.e. no SODE chunk was encountered after the preceding CHDR, IEND, PEND, or DEND chunk), the chunk will be treated as if it had been preceded by a SODE chunk with source=0, destination=0, source ID and destination ID omitted.

The DHDR chunk introducing a PND stream must be preceded by a SODE chunk with a valid source ID.

4.2 Ancillary composite frame chunks

4.2.1 gPLT Global Palette

This chunk may be used to suggest a reduced global palette to be used when the display device is not capable of displaying the full range of colors present in the images. If present, it provides a recommended set of colors, with alpha and frequency information, that may be used to construct a reduced palette to which the truecolor image may be quantized.

The format of this chunk is identical to that of the [proposed] sPLT PNG chunk. The chunk's contents are a zero-byte-terminated text string that names the palette, followed by a series of palette entries, each a ten-byte series, containing five unsigned integers:

```
    name:       n bytes  (ASCII text)
    null byte   1 byte   (terminator)
```

```
red:       2 bytes (0 = black, 65535 = red)
green:     2 bytes (0 = black, 65535 = green)
blue:      2 bytes (0 = black, 65535 = blue)
alpha:     2 bytes (0 = fully transparent,
                    65535 = fully opaque)
frequency: 2 bytes (relative frequency of occurrence)
...
```

There can be any number of entries; a decoder determines the number of entries from the remaining chunk length after the null-terminated "name" string. This length not divisible by ten is an error. Entries must appear in decreasing order of "frequency".

The "name" (e.g. "256 color including Macintosh default", "256 color including Windows-3.1 default", "50-color rgb palette for use with early versions of Mosaic") identifies the palette, which may permit applications or people to choose the appropriate one when more than one suggested palette appears in a PNF stream. The "name" string must consist only of printable ASCII characters and may not have leading or trailing blanks, but may have single embedded blanks. There must be at least one and no more than 79 characters in the name. Names are case-sensitive. Decoders should filter out any nonprintable characters, especially the ESC character, in the "name" string before displaying it, to avoid possible security hazards.

The red, green, and blue values are not premultiplied by alpha, nor are they precomposited against any background. A decoder can build a palette by compositing those palette entries against any background color or set of background colors that it chooses.

Each frequency entry is proportional to the approximate fraction of pixels in the images that are closest to that palette entry, without regard to any compositing against a background palette. The exact scale factor is chosen by the encoder, but should be chosen so that the range of individual values reasonably fills the range 0 to 65535. It is acceptable to artificially inflate the "frequency" values for "important" colors such as those in a company logo or in the facial features of a portrait. Zero is a valid value for frequency.

The palette uses 16 bits (2 bytes) per value regardless of the image bit depth specification. Decoders wishing to construct 8-bit palettes can accomplish this by scaling down the RGB entries to 8 bits, as described under "bit depth rescaling" in the PNG specification.

If the file gamma value for a subimage is different from the default gamma value from the FHDR chunk, decoders will need to gamma-correct the image samples before quantizing them to the gPLT palette.

Multiple gPLT chunks, with different names, are allowed within a composite frame description. If present, they must appear prior to any IHDR, DHDR, or PHDR chunk in the composite frame. The gPLT chunk may appear for any color type. When a subimage contains a PLTE or sPLT suggested palette, the gPLT data takes precedence.

4.2.2 oFFs Composite frame offset

Same as PNG, offsets the entire composite frame. If a subimage also contains an oFFs chunk, the values from both oFFs chunks are added together with the LOCA value to form a total offset for the subimage.

Only one oFFs chunk is allowed within a composite frame description, and, if present, it must appear prior to any IHDR, DHDR, or PHDR chunk in the composite frame.

4.2.3 tEXt, zTXt Text chunks

Same as PNG. *[Should we also allow the tIME chunk here?]*

5 Retaining image data

When dependent frames (PND streams or "dependent" composite frame streams) are present, the decoder must retain information about the previous frame for use in decoding the dependent frame. It is never necessary to retain information from frames earlier than the previous frame, except for the original background, which must be retained for the entire duration of the PNF stream if it is required.

When the encoder knows that image data will not be needed by subsequent frames, it can make life easier for decoders by using the "ok_to_discard" field of the FHDR chunk or by using the dISC chunk, and by proper use of the destination_id field of the SODE chunks in composite frames.

When the encoder knows that all subsequent images will completely fill the display and do not use transparency, the background_source field of the FHDR chunk can be used to inform the decoder that it does not have to retain the background.

To retain a subimage from the previous composite frame for use in a later composite frame, but not display it in the present frame, the SODE chunk can be used to pass it along to the next frame without displaying it.

6 Security Considerations

Security considerations are addressed in the basic PNG specification.

The gPLT chunk contains a "name" field that might be printed or displayed as text by some applications. As with the tEXt chunk, any non-printable characters in the gPLT "name" field, especially the ESC character, should not be displayed directly.

No known additional security concerns are raised by this format.

Detection of corrupted file transfers can be improved even beyond that available in PNG by using the FHDR max_chunk_size field to determine whether any chunk length (except for that of FHDR itself, which has a known length that can be checked) is unreasonably large.

7 Appendix: Examples

7.1 Example 1: Simple movie

```
\211 P N F \r \n ^z \n  # PNF signature
FHDR 720 468     # width and height
     20 65536  # 20 frames, max chunk length = 65kbytes
     30  3 60  # 10 frames per second, duration 60 ticks
     77000  8  # default gamma is 0.77, max_bit_depth 8
     2 0 0 0 0 # Background not required, not OK discard
tEXtTitle\0Sample Movie

SEEK 0 n1
IHDR 720 468 ...
IDAT ...
IEND

DHDR 1 1 0  # A PNG-delta frame
IDAT ...
DEND

DHDR 1 1 0  # Another PNG-delta frame
IDAT ...
DEND

SEEK n1 n2      # Ok to restart here because a
                # complete PNG frame follows
IHDR 720 468
IDAT ...
IEND

DHDR 1 1 0    # another PNG-delta frame
IDAT ...
DEND

SEEK n2 0
FEND            # end of PNF stream
```

7.2 Example 2: Single composite frame

Here's an example single-composite-frame PNF, which takes a grayscale image and draws it side-by-side with a false-color version of the same image:

```
\211 P N F \r \n ^z \n # PNF signature
FHDR 1024 512 1 8192 # width, height, nframes, maxchunklen
     1 0 0    # frame duration can be zero since there's
              # only one frame but ticklength must be nonzero
     100000   # default gamma value is 100000 (gamma=1.0)
     16       # depth 16
     1 64 64 192  # sky blue background
     1        # ok to discard
CHDR 1024 512 0 0 0  # Initial composite frame, 1024 x 512
LOCA 6 6             # Location of first subimage
SODE 0 2 1           # New object 1, keep for later use
IHDR 500 500 16 0 .. # A 16-bit graylevel image
gAMA 50000
IDAT ...
IEND                 # End of subimage

SODE 2 0 1           # Reload object 1, discard afterwards
LOCA 518 6           # Location for second subimage.  Note
                     #    that SODE-LOCA order doesn't matter.
DHDR 1 1 0
IHDR 500 500 16 0 .. # Png-delta, inherits gAMA and IDAT
                     #    from object 1
tEXtComment\0The faLS chunk is described in ftp://swrinde....
faLS ...             # Apply pseudocolor to previous subimage
                     # No IDAT; pixels don't change
IEND
DEND                 # End of subimage

LOCA 900 400         # Overlay near lower right-hand corner
IHDR 101 101 2 3 ... # SODE can be omitted when the subimage
                     #    doesn't depend on another and
                     #    nothing depends on it.
gAMA 50000           # We need a new gAMA, though, because
PLTE ...             #    there's no "source ID" for object.
tRNS ...             # It's transparent (maybe a logo)
IDAT ...             # Note that the color type can differ
IDAT ...             #    from that of the other objects.
IEND                 # End of subimage

CEND                 # End of composite frame
FEND                 # End of PNF stream
```

7.3 Example 3: Movie with sprites

Here's another movie, illustrating the use of PND streams as sprites

```
\211 P N F \r \n ^z \n  # PNF signature
FHDR 512 512       # Start of PNF stream
     30 3 3000     # 10 frames/sec, not more than 100 sec
     50000 8       # default_gamma 0.5, max_bit_depth 8
     2 0 0 0       # don't need background
     0             # not ok to discard
CHDR 512 512 0 0 0 # First frame
LOCA 0 0           # Location for object 1
SODE 0 1 1         # define object 1  and export to next frame
PHDR 512 512 ...   # it's a full-display PNP image
etc                # chunks according to PNF spec
PEND
LOCA 300 200     # Location for object 2
SODE 0 1 2       # define object 2 and export to next frame
IHDR 32 32 ...   # It's a small PNG
gAMA 50000
IDAT ...
IEND
CEND             # end of frame

CHDR 512 512 0 0 1 # Next frame (repeat this CHDR-CEND
                   #   sequence with different locations to
                  #   move the objects around)
LOCA 0 0         # New location for object 1 is still 0,0
SODE 1 1 1 1     # Retrieve object 1 from previous frame,
                  #    export to next
DHDR 1 1 0       # A completely empty DHDR-DEND just
                  #    redisplays the object
DEND             #    at the new location
LOCA 310 205     # New location for object 2
SODE 1 1 2 2     # Retrieve object 2 from previous frame,
                  #    export it to the next
DHDR 1 1 0       # Another empty DHDR-DEND to redisplay
DEND             #    object 2 unchanged
LOCA 400 500     # Location for another copy of object 2
SODE 2 1 2 3     # Reuse object 2 from this frame,
                  #    export it as object 3
DHDR 1 1 0       # Another DHDR-DEND
tRNS ...         # Make it semitransparent
DEND
CEND               # End of frame

CHDR 512 512 0 0 1 #  Another frame
etc.
CEND
etc.               # More frames
FEND               # End of PNF stream
```

7.4 Example 4: "Fading in" a transparent image

The opaque parts of this image will "fade in" gradually. This technique won't work with color_type 4 or 6 images that have partially transparent pixels. You would use a series of PND streams with IDAT chunks, instead, that add the desired amount to each individual alpha sample but have zeroes in the color component deltas. You can, however, "fade out" such images with the `fADE` chunk.

```
\211 P N F \r \n ^z \n # PNF signature
FHDR 64 64 16  # width, height, nframes
     8192      #  maxchunklen
     30 6 140  # tick length, frame and total duration
     50000     # default gamma
     8         # max bit depth 8
     0         # use application supplied background
   192 192 192 # "browser gray" default background
     0         # not ok to discard
IHDR ...    # PNG header
PLTE ...
tRNS ...    # Entries are zero for the transparent color
            # and 16 for the nontransparent ones.  They
            # will be barely visible)
IDAT ...
IEND
dURa
DHDR 1 1 0
fADE 2 16   # Add 16 to alpha for all nontransparent
DEND        # colors
DHDR 1 1 0  # Repeat
fADE 2 16
DEND
etc.        # Repeat DHDR-fADE-DEND 13 more times.  The
            # opaque colors will end up with alpha=255
            # and the transparent ones will still be 0.
dURa 60     # Hold the last frame for at least 60 ticks
            # (2 sec).  Applications might show it longer,
            # or they might ignore dURa; it's ancillary.
FEND        # end of PNF
```

7.5 Example 5: Storing three-dimensional images

In this example, we store a series of twenty-four 150 x 150 x 150 blocks of 8-bit voxels. Each block is stored as a composite frame with the first subimage being a PNG whose pixels represent the top layer of voxels, which is followed by 149 PND subimages representing the rest of the layers of voxels. Only one "object" is defined, through which the basis image is passed along from PNG to PND to PND. This example also illustrates the use of unregistered ancillary chunks that describe the x, y, and z scales and pixel calibration.

```
\211 P N F \r \n ^z \n # PNF signature
FHDR 150 150 24  # width, height, nframes
     65000       #  maxchunklen (doesn't have to be 2^n)
     30 0 0      # tick length, duration (can be zero)
     100000      # default gamma (voxel data is linear)
     8           # max bit depth 8
     2 0 0 0     # background not needed
     0           # not ok to discard

tEXtTitle\0Weather modeling results - temperature distribution on July 15
tEXtComment\0The xsCL, ysCL, zsCL, and tsCL chunks in this file are
 written according to the PNG Sci-vis chunks specification version
0.960816
 available at ftp://swrinde.nde.swri.edu/pub/png-group/documents/

tsCLTime (hours)\0 0\0 24 # see proposed sci-vis chunks

SEEK 0 3588720    # 3588720 bytes to the next SEEK chunk
CHDR 150 150 0 0 0 # initial composite image
zsCLHeight (kilometers)\0 0\0 15
IHDR 150 150 8   # width, height, bit depth for top layer
     0 0 0 0     # color, comp, filter, interlace
xsCLkilometers\0 0\0 150 # sci-vis "xsCL" chunk
ysCLkilometers\0 0\0 150 # sci-vis "ysCL" chunk
pcALDegrees Celsius\0 0\0 45  # sci-vis "pcAL" chunk
IDAT ...
IEND

DHDR 1 1 0  # PNG pixel subtraction, copysafe
            # IHDR is omitted; everything matches top
IDAT ...    # no need to repeat pcAL, xsCL and ysCL
DEND        # IEND is also omitted

etc.   # repeat DHDR through DEND 148 more times
CEND   # end of first block

etc.   # Repeat SEEK through CEND 19 more times
       # Must repeat the x, y, zSCL chunks because all
       # data is forgotten when SEEK is encountered

SEEK 2285321 0

FEND   # end of PNF
```

8 Credits

Contributors' names are presented in alphabetical order:

- Mark Adler, madler@alumni.caltech.edu
- Thomas Boutell, boutell@boutell.com
- John Bowler, jbowler@megamed.com
- Christian Brunschen, cb@df.lth.se
- Glen Chapman, glenc@clark.net
- Adam M. Costello, amc@cs.wustl.edu
- Lee Daniel Crocker, lee@piclab.com
- Peter da Silva, peter@starbase.neosoft.com
- Andreas Dilger, adilger@enel.ucalgary.ca
- Oliver Fromme, fromme@rz.tu-clausthal.de
- Jean-loup Gailly, gzip@prep.ai.mit.edu
- Chris Herborth, chrish@qnx.com
- Alex Jakulin, alex@hermes.si
- Neal Kettler, kettler@cs.colostate.edu
- Tom Lane, tgl@sss.pgh.pa.us
- Alexander Lehmann, alex@hal.rhein-main.de Chris Lilley, chris@w3.org
- Dave Martindale, davem@cs.ubc.ca
- Owen Mortensen, ojm@csi.compuserve.com
- Glenn Randers-Pehrson, glennrp@arl.mil or randeg@alumni.rpi.edu
- Greg Roelofs, newt@uchicago.edu
- Willem van Schaik, gwillem@ntuvax.ntu.ac.sg
- Guy Schalnat
- Paul Schmidt, pschmidt@photodex.com
- Smarasderagd, smar@reptiles.org
- Thomas R. Tanner, ttehtann@argonet.co.uk
- Guido Vollbeding, guivol@esc.de
- Tim Wegner, 71320.675@compuserve.com
- Alaric B. Williams, png@abwillms.demon.co.uk

Trademarks:

- Macintosh is a trademark of Apple Computer, Inc.
- Windows 3.1 is a trademark of Microsoft Corporation.

Author's Address

Glenn Randers-Pehrson
U.S. Army Research Laboratory
ATTN: AMSRL-WT-TD
Aberdeen Proving Ground, MD 21005-5066

Phone: (410) 278-6554

EMail: glennrp@arl.mil or randeg@alumni.rpi.edu

End of PNF Specification. Expires 16 February 1997